



MODUCOATINGS

NANO GALV® COATING PRODUCT DATASHEET

NanoGalv is a zinc-nickel nanolaminate (nanostructured) technology that provides excellent corrosion resistance in coastal and marine environments across a broad range of fastener applications.

COATING THICKNESS	8 microns minimum on significant surfaces
COATING AND INDUSTRY DESIGNATIONS	<ul style="list-style-type: none">• ASTM F1941 Fe/Zn-Ni 8BN• ASTM B841 Class 2 Type AN• ASTM B1025 Grade 8 Type A/AN
COEFFICIENT OF FRICTION (COF) (ISO 16047 K-FACTOR)	0.15 +/- 0.04 with lubricant
OPERATING TEMPERATURE	-148°F to 401°F (-100°C to 205°C) - Constant exposure -148°F to 751°F (-100°C to 400°C) - Intermittent exposure
OPERATING ENVIRONMENT	Coastal & Offshore Marine (above splash zone)
MARKET APPLICATIONS	Infrastructure, Marine, Oil and Gas, Transportation
SALT SPRAY (ASTM B117)	>3,000 hours
CYCLIC CORROSION (GMW 14872)	120 cycles with stress
COATING ADHESION (ASTM B571)	Pass: Bend, Burnish, Heat/Quench and Impact methods
HYDROGEN EMBRITTLEMENT (ASTM F519)	Pass 200h sustained load test
SUBSTRATE COMPATIBILITY	<ul style="list-style-type: none">• Carbon steel and low alloy steels.• High strength steels are baked per ASTM B850
INSTALLATION COMPATIBILITY	Carbon and alloy steel connections
RECOMMENDED TORQUE VALUES	Available upon request



8317 Willow Place Drive North
Houston, TX 77070
sales@moducoatings.com

MODUCOATINGS.COM

© ModuCoatings 2026. NanoGalv is a registered trademark of Modumetal Inc.

Revised May 2026